

Without sensor but with what it takes. Halogen floodlight H 150, ideal for building fronts, driveways and vulnerable spots, perfect addition to the HS 150, halogen enclosure tilts through 150° and turns through 80°, high-quality and powerful ceramic reflector, 150 W max., includes ECO halogen linear lamp.

Perfect addition to the HS 150.

The H 150 halogen floodlight was developed specifically for connecting to sensor-switched halogen floodlights with external switch output, e.g. the HS 150. The halogen floodlight is rated for a maximum of 150 W, .a 125 W ECO linear halogen lamp is included. It comes with an enclosure in sturdy, tough die-cast aluminium and a ceramic reflector with very good thermal and optical properties. The reflector head can be tilted through 150° and swivelled through 80° for setting reach with pinpoint accuracy.

Technical specifications Outdoor floodlight H 150 White	
European Article Number (EAN)	4007841631215
Dimensions(h x w x d):	180 x 156 x 166 mm
Voltage	230-240 V/50 Hz
Output	max. 150 W/R7s linear halogen lamp
Floodlight positioning range	80° horizontally, 150° vertically
IP rating	IP44
Protection class	I
Material	UV-resistant plastic and aluminium floodlight head
Version	White
With lamp	yes, 125 W ECO linear lamp

Application

Fronts of buildings, driveways and vulnerable spots, ideal addition to HS 150