

Timeless classic with efficient LEDs. Sensor-switched outdoor light STEINEL GL 60 LED, ideal for gardens, drives or pathways. 8.6 W STEINEL LED lighting system, 812 lm, 360° infrared sensor with 8 m reach, including basic light function, soft light start and optional manual override.

STEINEL LED lighting system.

Efficient, long-lasting and trendsetting. More quality of life, more safety and security and more energy saved with intelligent sensor and LED technology from STEINEL.

Light ON/OFF – automatically.

Highly innovative sensors respond to movements and light levels, automatically and instantaneously switching the light ON and OFF again after a preselected time.

Intelligent lighting in your garden, on paths and along your drive. Our popular model scores with its clean-cut, sleek design, impressive detection quality and intelligent distribution of light. An energy-boosting benefit with warm-white light from STEINEL's 8.12-W LED lamp. The timeless classic also provides the last word in selectable functions for tailor-made performance: sensor detection range up to 8 m with a 360° angle of coverage, twilight threshold adjustable from 2 – 2,000 lx and time threshold from 5 sec. to 15 min. Plus: soft light start that is easy on the eyes, 0 – 50% basic light level and 4-hour manual override. As its base can be shortened, the GL 60 LED can also be used as a bollard light. All in all, the sensor-switched outdoor light provides unbeatable quality, service life and energy efficiency. Incidentally, STEINEL vouches for this with a 3-year functional warranty.

Technical specifications GL 60 LED	
European Article Number (EAN)	4007841007881
Voltage	230-240 V/50 Hz
Sensor type	Passive infrared
Output	8.6 W max.
Brightness	812 lm
Efficiency	94.4 lm/W
Light colour	CC001168

Colour rendering	CC001113
LED life expectancy	25000 h
Detection angle	360° with 20° angle of aperture
Capability of masking out individual segments	Yes
Reach	8 m max.
Response brightness	2-2000 lx
Time setting	5 sec. - 15 min.
Basic light level	0 % - 50 %
Soft light start	Yes
Manual override	4 hours, selectable
IP rating	IP44
Protection class	II
Lamp replaceable	Yes
Material	Stainless steel
Temperature range	CC001169
With lamp	CC001133

Application

ideal for gardens, drives or pathways